

HiPace 300 H

Turbomolecular vacuum pumps



Reliable

Best-in-class hybrid bearing technology, long life cycle, maximum uptime

Quiet

Low noise and vibration levels thanks to patented laser balancing technology

High performance

Best compression ratio for light gases, perfectly suited for high and ultra-high vacuum applications

Accessories

- Electrical adapter
- Mains cable
- Connecting cable
- Various fieldbus systems
- Power supply kit and display unit
- Mounting kit
- Safety valve
- Venting accessories
- Power failure venting unit
- Vibration damper

HiPace 300 H

Turbomolecular vacuum pumps



Dimensional drawing

Pumping speed

The following technical values refer to ISO Hz

HiPace 300 H with TC 110	
Pumping speed for Ar	255 l/s
Pumping speed for He	255 l/s
Pumping speed for H#	220 l/s
Pumping speed for N#	260 l/s
Compression ratio for Ar	$1 \cdot 10^{13}$
Compression ratio for He	$2.5 \cdot 10^{\#}$
Compression ratio for H#	$1 \cdot 10^{\#}$
Compression ratio for N#	$1 \cdot 10^{13}$
Gas throughput at final rotational speed for Ar	0.5 hPa l/s
Gas throughput at final rotational speed for He	3.5 hPa l/s
Gas throughput at final rotational speed for H#	10 hPa l/s
Gas throughput at final rotational speed for N#	1.5 hPa l/s
Forevacuum max. for N#	30 hPa
Run-up time	3.5 min
Communication interfaces optional	Profibus, Devicenet, Semi E74
Communication interfaces standard	RS-485, remote
Mounting orientation	arbitrary
Sound pressure level (EN ISO 2151)	50 dBA
Weight approx.	6.2 kg
Gas inlet	DN 100 ISO-K/ISO-F/CF-F
Gas outlet	DN 16 ISO-KF /G 1/4"

HiPace 300 H

Turbomolecular vacuum pumps



Do you want to know more

Please contact us!
contact@pfeiffer-vacuum.com or +1-800-248-8254



Contact form



Call us now